

**In the Claims:**

1. (Currently Amended) A method for improving the perceived resolution of a color matrix display with at least one pixel, comprising the steps of

subdividing an incident color channel signal ( $R$ ) to said pixel into a first and second signal component,

applying a gain factor to one of said signal components, the gain factor being based upon the incident color channel signal's contribution to total luminescence of the display, and

subsequently recombining said first and second signal components into an exiting, modified color channel signal.

2. (Original) A method according to claim 1, wherein said first and second signal components are a low-pass component and a high-pass component, respectively.

3. (Currently Amended) A method according to claim 1 ~~claim 2~~, wherein the first and second signal components are respectively a low-pass component and a high-pass component, and

applying a gain factor to one of said signal components includes applying the said gain factor only is applied to said high-pass component.

4. (Previously presented) A method according to claim 2, wherein said low-pass component is realized by means of a low-pass filter, and said high-pass component is realized by means of a high-pass filter, said low-pass and high-pass filters being complementary.

5. (Currently Amended) A method according to claim 1, further comprising the step of:

determining providing the gain factor for the one of said signal components based upon the incident color channel signal's contribution to total luminescence of the display, ~~so that~~ the gain factor being is inversely proportional to the contribution of the color channel to the total luminance of the color matrix display.

6. (Previously presented) A method according to claim 1, further comprising the step of:

transmitting said exiting, modified color channel signal to a delay and up- or downsampling block in order to provide the modified color channel signal with a suitable delay and scaling.

7. (Currently Amended) A color matrix display device having at least one pixel, said pixel being arranged to be controlled by means of an applied color channel signal, the display device having a control unit comprising:

[-] a subdivision unit, for subdividing an incident color signal into a first and second signal component,

[-] a gain factor application unit, for applying a gain factor to one of said components, the gain factor being based upon the incident color channel signal's contribution to total luminescence of the display, and

[-] a recombination unit, for subsequently recombining said first and second signal components into an exiting, modified color channel signal, being used to control said pixel.

8. (Currently Amended) A color matrix display device as in claim 7, ~~being arranged to perform the method according to claim 1~~ wherein the control unit determines the gain factor based upon the incident color channel signal's contribution to total luminescence of the display.

9. (Previously presented) A method according to claim 1, wherein the step of subdividing includes subdividing each of separate color channel signals for an image into a first and second signal component.

10. (Previously presented) A method according to claim 1,  
wherein the step of subdividing includes subdividing each of separate color channel signals for an image into a first and second signal component, and

wherein applying a gain factor includes applying a gain factor to each separate color channel signal that is inversely proportional to the contribution of said separate color channel signal to the total luminance of the color matrix display.

11. (Previously presented) A method according to claim 1, wherein  
the step of subdividing includes subdividing a number N of different color channel signals, and  
the step of applying a gain factor includes applying a gain factor, for each color channel signal, that is about equal to the value of  $1/N$  multiplied by the reciprocal contribution of the channel signal to the total luminance of the color matrix display.

12. (Currently Amended) A color matrix display device for displaying images, the device comprising:

- a plurality of pixels controlled by applied color channel signals; and
- a controller including
  - a subdivision unit to subdivide, for separate color channel signals, each color channel signal into a first and second signal component,
  - a gain factor application unit to apply, for each color channel signal, a gain factor to one of said components, the gain factor having a value that is determined from, and inversely proportional to, the contribution of the color channel signal to the total luminance of the color matrix display device, and
  - a recombination unit to recombine, for each color channel signal, said first and second signal components into a modified color channel signal that is used to control said plurality of pixels.

13. (New) A method according to claim 1, wherein applying a gain factor includes applying a gain factor that removes a visible aliasing term from the incident color channel signal.

14. (New) A method according to claim 1, wherein applying a gain factor includes applying a gain factor that sets constants of a visible aliasing term for the incident color

channel signal to zero to remove a visible aliasing term from the incident color channel signal.

15. (New) A device according to claim 12, wherein the gain factor application unit is configured and arranged to apply the gain factor that removes a visible aliasing term from the incident color channel signal.

16. (New) A device according to claim 12, wherein the gain factor application unit is configured and arranged to apply a gain factor that sets constants of a visible aliasing term for the incident color channel signal to zero to remove a visible aliasing term from the incident color channel signal.